

# Mining and construction

**FMA**

A HIGH TECH. SPECIAL ATTACHMENT MANUFACTURER



**TIRE HANDLER TH2200**

# Mining and construction

**FMA**

A HIGH TECH. SPECIAL ATTACHMENT MANUFACTURER

## SPECIFICATIONS

- Maximum lifting capacity: 1.500Kg.
- Tire sizes accepted: 29.5 R29
- Maximum opening of the arms: 2.120mm
- Minimum opening of the arms: 1.050mm
- Rotation of the transverse arm: 35° izq. / 35° der.
- Vertical displacement of the carriage: 485mm.
- Lateral displacement of the carriage: 100mm.right. / 100mm left.
- Wheel rotation angle: 45° right. / 45° left.
- Translation speed: 0 a 14m/min.
- Tensile strength: 938Kg.
- Estimated weight: 1.580Kg
- Power supply: 380/450/600VAC.

## TIRE SIZE

- 35/65R33
- 24R49
- 29.5R29
- 18.00 R25

## STANDARD EQUIPMENT

- Parking brake.
- Operation of commands by wireless remote control.
- Proportional control for all commands.
- Toothed plates for tyre grip.
- Solid wheels.
- Rubber-coated metal front wheels.
- Operating lights.
- Beacon.
- Audible motion alarm.
- Wheel protection bar.
- Emergency hydraulic check valves.
- Wireless video camera.
- Operating, Maintenance and Spare Parts Manuals.

## OPTIONAL EQUIPMENT

- Wired remote control.

**TIRE HANDLER TH2200**